# Technical data sheet

#### Clamp clip 2056, H-foot, single, metal pressure trough, A4



**Item number: 1188521** 



Clamp clip with hammerhead foot, metal pressure trough with rounded edges to protect the cable. For vertical and horizontal mounting of 1 single cable on a C-profile rail. For a slot width of 16–17 mm. With 1-start screw thread on pressure trough, universal hexagonal screw head WAF10, with slot and cross recess. Suitable for mounting indoors and outdoors. We recommend the use of a countertrough.



A4

Stainless steel

2B

Bright, treated

#### Master data

Item number	1188521
Туре	BS-H1-M-12 A4
Description 1	Clamp clip 2056
Manufacturer	OBO
Dimension	8-12mm
Material	Stainless steel
Surface	Bright, treated
Surface standard	
Smallest sales unit	100
Unit of quantity	Piece
Weight	3.506 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	0,2436 kg COe / 1 Piece

## **Technical data sheet**

## Clamp clip 2056, H-foot, single, metal pressure trough, A4



**Item number: 1188521** 



#### **Technical data**

Number of cables/pipes  Maintain electrical functions For pipe diameter, max.  For pipe diameter, min. for rail with slot width (with interval), max. for rail with slot width (with interval), min.  Thread  Halogen-free Length of external dimensions Max. Tightening torque With metal trough  1 yes 12 mm 8 mm 17 mm 16 mm 16 mm 18 mm 19 mm 19 mm 10 mm 10 mm 10 mm 10 mm 10 mm 11 mm 12 mm 12 mm 13 mm 14 mm 15 mm 16 mm 17 mm 18 mm 18 mm 19 mm 10 m
For pipe diameter, max.  For pipe diameter, min. for rail with slot width (with interval), max.  for rail with slot width (with interval), min.  Thread  Halogen-free  Length of external dimensions  Max. Tightening torque  12 mm  8 mm  17 mm  16 mm  M6  Halogen-free  yes  Length of external dimensions  3 Nm
For pipe diameter, min. for rail with slot width (with interval), max. for rail with slot width (with interval), min. Thread Halogen-free Length of external dimensions Max. Tightening torque  8 mm 17 mm 16 mm M6 Halogen-free yes Length of external dimensions Max. Tightening torque  3 Mm
for rail with slot width (with interval), max.  for rail with slot width (with interval), min.  Thread  Halogen-free  Length of external dimensions  Max. Tightening torque  17 mm  M6  M6  W6  Halogen-free  28 mm  Max. Tightening torque  3 Nm
val), max. for rail with slot width (with interval), min. Thread M6 Halogen-free yes Length of external dimensions 28 mm Max. Tightening torque 3 Nm
val), min.  Thread M6  Halogen-free yes  Length of external dimensions 28 mm  Max. Tightening torque 3 Nm
Halogen-free yes Length of external dimensions 28 mm Max. Tightening torque 3 Nm
Length of external dimensions Max. Tightening torque  28 mm 3 Nm
Max. Tightening torque 3 Nm
With motel trough
With metal trough yes
Mounting type Profile rail
Slot width 10 mm
Clamping range D, max. 12 mm
Clamping range D, min. 8 mm
Surface addition Untreated
Material addition Rustproof steel