

# Technical data sheet

## Quick clip, black

Item number: 2149575



Flush-mounted clip to accept metric steel armoured pipes and heavy-duty insulating pipes, as well as Quick-Pipe® electrical installation pipes. Universal fastening options on walls and ceilings, both in indoor and protected outdoor areas. With slot for side alignment during mounting with wood screw or knock-in anchor. Toolless pipe mounting. Can also be arranged with OBO Multi-Quick or proQuick clip. M16 - M32 size can be screwed onto M6 thread. Recommended fastening spacing 50–60 cm, for max. extraction values F at a room temperature of 20 °C, see the table.



PP Polypropylene

### Master data

|                                    |                          |
|------------------------------------|--------------------------|
| Item number                        | 2149575                  |
| Type                               | 2955 M40 SW              |
| Description 1                      | Quick clip               |
| Manufacturer                       | OBO                      |
| Dimension                          | M40                      |
| Colour                             | Jet black; RAL 9005      |
| Material                           | Polypropylene            |
| Smallest sales unit                | 50                       |
| Unit of quantity                   | Piece                    |
| Weight                             | 0.835 kg                 |
| Weight unit                        | kg/100 pc.               |
| CO2 Footprint (GWP) Cradle-to-Gate | 0,0353 kg CO2e / 1 Piece |


# Technical data sheet

Quick clip, black

Item number: 2149575



## Dimensions



|             |         |
|-------------|---------|
| Dimension A | 57.3 mm |
| Dimension B | 16 mm   |
| Dimension C | 26 mm   |
| Dimension D | 39.2 mm |
| Dimension E | 11 mm   |
| Dimension F | 4.6 mm  |
| Dimension h | 12 mm   |
| Dimension H | 51 mm   |

## Technical data

|                         |                                              |
|-------------------------|----------------------------------------------|
| Expandable              | yes                                          |
| Number of cables/pipes  | 1                                            |
| Pull-out value          | 110 N                                        |
| Fastening type          | Screw hole                                   |
| Closed                  | no                                           |
| Halogen-free            | yes                                          |
| With inlay              | no                                           |
| Nominal size            | M40                                          |
| ROHS-conformant         | yes                                          |
| Quick clip installation | Durchgangsloch, auf M6 Gewinde aufschraubbar |
| UV-resistant            | no                                           |