

Technical data sheet

Support rail MagicFix

Item number: 6426302



Support rail for light cable trays, mesh cable trays and cable ladders for the creation of pendulum suspensions and centre suspensions. Tool-free fastening through clamp mount for mesh cable trays or additional quick connector MagicFix for trays and ladders. Alternatively, screw fastening possible. Suspension with suspension strips Magic Fix. Tool-free fastening of the support rail on suspension strips through fastening straps.



St

Steel

FS

Strip galvanised

Master data

Item number	6426302
Type	TSM 100 FS
Description 1	Support rail MagicFix
Manufacturer	OBO
Dimension	22x45x171
Colour	zinc
Material	Steel
Surface	Strip galvanised
Surface standard	DIN EN 10346
Smallest sales unit	1
Unit of quantity	Piece
Weight	13.3 kg
Weight unit	kg/100 pc.


Technical data sheet

Support rail MagicFix

Item number: 6426302



Dimensions



Length	146 mm
Width	46 mm
Height	22 mm
Dimension L	146 mm
Dimension L2	171 mm
Maß sH	7x28 mm

Technical data

Version for	Support profile
Maintain electrical functions	no
Suitable for mesh cable tray	yes
Suitable for cable ladder	yes
Suitable for cable tray	yes
Hole diameter	10.5 mm
Material thickness	1.5 mm
ROHS-conformant	yes
Rustproof steel, pickled	no
Hinged	no
Permitted temperature range, max.	120 °C
Permitted temperature range, min.	-20 °C
Adjustable	no

Loads

Safe working load of suspended installation with ASM for cable trays (SWL)	1 kN
Safe working load of suspended installation with ASM for mesh cable trays (SWL)	1 kN